

TIME CHARTER

NAME OF VESSEL	MV ASTURCON	
TYPE OF VESSEL	CRANED DOUBLE HULL SINGLEDECK BULKCARRIER BOXSHAPED IN HOLDS 2, 3, 4	
DWAT (SUMMER/WINTER)	36.063 MTS	34.968 MTS
DRAFT (SUMMER/WINTER)	10,304 M	10,089 M
BUILT (MONTH/YEAR) / YARD	MAY 2014 / CSC JINLING SHIPYARD, NANJING/CHINA	
FLAG / PORT OF REGISTRY	THE MARSHALL ISLANDS / MAJURO	
CLASSIFICATION	ABS	
IMO NO.	9646730	
L.O.A. / L.B.P.	180,00 M	176,75 M
BEAM	30,00 M	
MOULDED DEPTH	14,70 M	
T.P.C. ON SSW	50,81 MTS	
INTERNAT./SUEZ/PANAMA GT/NT:		
INTERNAT. GT/NT	24.247	12.032
SUEZ CANAL GT/NT	25.881	25.129
PANAMA CANAL NT	20.230	

HOLDS	
NUMBER OF HOLDS/HATCHES	5 / 5
HOLD VENTILATION	NATURAL

HOLD DIMENSIONS	No.	LENGTH		BREADTH		HEIGHT	
	1	27,40	M	26,00	M	15,10	M
	2	26,30	M	26,60	M	15,50	
	3	26,20	M	26,60	M	15,50	
	4	26,20	M	26,60	M	15,50	
	5	28,30	M	26,60	M	15,10	

TANK TOP DIMENSIONS (L x B):	No.	LENGTH		BREADTH			
	1	27,40	M	7,75	M (FWD)	26,00	M (AFT)
	2	26,30	M	26,60	M		
	3	26,20	M	26,60	M		
	4	26,20	M	26,60	M		
	5	28,30	M	26,00	M (FWD)	6,90	M (AFT)

HOLDWISE GRAIN/BALE CUBIC BREAKDOWN IN CBM (100% INCL HATCHES)

No.	GRAIN	BALE
1	7.948	7.819
2	9.790	9.525
3	9.782	9.517
4	9.783	9.517
5	9.428	9.276
TOTAL:	46.731	45.654

HATCHES	
TYPE OF HATCHCOVERS	END FOLDING STEEL HATCHCOVER; HYDRAULICALLY OPERATED DOUBLE-SKIN CONSTRUCTION

HATCHCOVER DIMENSIONS	No.	LENGTH		BREADTH			
	1	16,00	M	18,70	M /	15,00	M
	2	19,20	M	20,30	M		
	3	19,20	M	20,30	M		
	4	19,20	M	20,30	M		
	5	19,20	M	20,30	M		

GEAR

TYPE OF CRANES SINGLE JIB, WIRE LUFFING, FULLY ELECTRICAL DRIVEN
 NUMBER / CAPACITY OF CRANES 4 X 30,5 MTS SWL

STRENGTH

WEATHER DECK HATCHES	2,5	MTS/M2	UNIFORM LOAD
UPPER DECK	4,0	MTS/M2	
TANK TOP	25,0	MTS/M2	UNIFORM LOAD

DISTANCE FROM WATERLINE TO TOP OF HATCH COAMING
 IN HEAVY BALLAST CONDITION FOR HOLD

No.	
1	10,2
2	9,9
3	9,6
4	9,2
5	8,9

IN LIGHT BALLAST CONDITION FOR HOLD

No.	
1	11,8
2	11,5
3	11,1
4	10,8
5	10,4

MAIN ENGINE (MAKER) DOOSAN, KOREA

SPEED / CONSUMPTION

LADEN ABOUT 13,5 knots ON ABOUT 21,0 mt IFO 380CST
 ABOUT 12,0 knots ON ABOUT 16,25 mt IFO 380CST

BALLAST ABOUT 13,5 knots ON ABOUT 18,5 mt IFO 380CST
 ABOUT 12,0 knots ON ABOUT 14,25 mt IFO 380CST
 Always including auxiliaries/boiler

IN PORT CONSUMPTION (BASIS 24 HRS)

IDLE	ABOUT 2,5 mts HFO
ALL GEAR WORKING	ABOUT 3,2 mts HFO

THE SHIP MAY CONSUME MGO WITH HER MAIN ENGINE WHEN STARTING/STOPPING ENGINES, ENTERING/LEAVING PORTS, DURING BAD AND/OR COLD WEATHER, DURING MANOEUVERING AND SAILING IN CONFINED AND/OR SHALLOW WATERS, RIVERS, CANALS AND/OR DRIFTING /BERTHING/UNBERTHING ETC.

SHIP MAY BURN ADDITIONAL BUNKERS WHEN BOILER IN USE, IN COLD WEATHER, OR DURING BALLASTING / DEBALLASTING OR BALLAST EXCHANGE VESSEL'S SPEED AND CONSUMPTION ARE WARRANTED ONLY BASIS AT LEAST 23 CONSECUTIVE HOURS NOON TO NOON UNDER GOOD WEATHER CONDITIONS, CALM SEA, NO ADVERSE CURRENTS, UP TO BEAUFORT SCALE FORCE 4 AND A COMBINED SEA- AND WAVEHEIGHT OF UPTO MAX 1,5M, UNRESTRICTED VISIBILITY AND NO CONGESTED WATERS / STRAITS / COASTAL WATERS OR WHILE FOLLOWING SLOW STEAM INSTRUCTIONS. "ABOUT" MEANS HAVING AN ALLOWANCE OF 0.5 KNOTS ON SPEED AND +5% ON BUNKERS' CONSUMPTION.'

PRIOR CHARTERERS TAKING VLSIFO, SPECS TO BE SENT TO HEADOWNERS FOR THEIR APPROVAL WHICH NOT TO BE UNREASONABLY WITHHELD.

FUEL OIL SPECIFICATIONS: ISO 8217:2017
 VLSFO 0.5%, LSMGO DMA STANDARDS AND CONFORM TO REGULATIONS 14&18 OF ANNEX VI MARPOL 73/78.

IF ISO 8217:2017 SPECIFICATIONS ARE NOT AVAILABLE THEN CHARTERERS SHALL HAVE THE OPTION TO SUPPLY FUEL ACCORDING TO ISO 8217:2010 SPECIFICATIONS WHICH TO CONFORM TO REGULATIONS 14&18 OF ANNEX VI MARPOL 73/78.

THE BUNKERS SHALL BE OF A STABLE AND HOMOGENEOUS NATURE, SUITABLE FOR MARINE USE AND FOR BURNING IN THE VESSEL'S ENGINES ACCORDING TO MAKERS RECOMMENDATIONS AND NOT TO CONTAIN ANY KIND OF TAR-OIL, CHEMICAL AND/OR OTHER LUBRICANTS.

No mixing of bunkers IN TANKS allowed.

Charterers have to fully comply with international, national and local Emission limits resp. rules, regulations, requirements and directives for main and auxiliary engines, as well as consumption of adequate bunker grades. THIS VESSEL IS A MEMBER OF A FUEL TESTING SYSTEM. SAMPLES ARE TO BE TAKEN DURING EACH BUNKERING AT VESSEL'S MANIFOLD.

TANK CAPACITIES (100%):

FUEL OIL	1.547	CBM
MGO/MDO TANK CAPACITY	291 / 110	CBM

THE BUNKER TANK CAPACITIES COULD BE AFFECTED DUE TO VESSEL HAVING TO TAKE SEPARATELY SPECIAL FUELS/GASOILS AS PER MARPOL REGULATIONS. ONLY 85% OF TANK CAPACITIES SHALL BE USED AND ALWAYS IN CLOSE COORDINATION WITH VESSEL'S MASTER.

FRESHWATER / CONSTANTS

FRESH/POTABLE WATER CAPACITY	181 / 68	CBM
------------------------------	----------	-----

CONSTANTS ABT 300.00 MTS EXCLUDING FRESHWATER. THE CONSTANTS COULD BE AFFECTED DUE TO VESSEL RETAINING ON BOARD HOLD CLEANING WATER AS PER MARPOL REGULATIONS.

OTHERS

REGISTERED OWNER & CONTRACTUAL PARTNER:

STALLION FIVE SHIPPING CO. S.A, MAJURO, THE MARSHALL ISLANDS (FOR C/P PURPOSES)

MANAGERS:

ARISTON NAVIGATION CORPORATION, PIRAEUS, GREECE

POOL MANAGER;

TMA BULK POOL INC, MARSHALL ISLANDS

COMMERCIAL MANAGER:

TMA BULK GMBH & CO. KG, HAMBURG, GERMANY

CALL SIGN V7CH7

LAST D.D./S.S. 2024

NEXT D.D./S.S. 2029

INSURANCE

P + I CLUB	GARD
H + M VALUE	USD 16.000.000

COMMUNICATION

E-MAIL	asturcon@aristonfleet.gr	
MAIN	+30 2112345447	(Bridge/Captain)
FX	+870 771369338	(Bridge/Captain)
FBB	+870 773062698	(Bridge/Captain)

SHAFT GENERATOR NO

ITF FITTED OR EQUIVALENT YES

GRAIN FITTED YES

CO2 FITTED YES

LOGS FITTED NO

AUSTRALIAN HOLD LADDERS FITTED YES

CONTAINER FITTED NO

HATCH COVERS FITTED WITH CEMENT HOLES YES

PERMANENT LASHING EQUIPMENT: YES (AN ADEQUATE NUMBER OF PERMANENT LASHING D-RINGS ARE FITTED ON SIDE BULKHEADS OF No.2, No.3 & No.4 CARGO HOLDS AND ADDITIONALLY AN ADEQUATE NUMBER OF HEAVY DUTY PAD EYES ARE PERMANENTLY FITTED ON MAIN DECK FROM FORE TO AFT SIDE.

ALL DETAILS AND FIGURES ARE TO BE CONSIDERED AS 'ABOUT'.

ADD Date: 02.12.2024 (KW)